

Unplasticised Polyvinyl Chloride (PVC-U) is the most widely used of all plastics used for pipe installations. It is rigid, versatile, and is suitable for both above or below ground installations.

It has excellent chemical resistance which, when combined with smoothness of bore, eliminates build up of scale and gives good flow characteristics. It is odourless and tasteless, and is suitable for conveying potable water and many food or dairy products.

PVC-U is suitable for use at temperatures from 0°C to 60°C at a wide range of operating pressures, depending upon the system chosen. It is lightweight and easy to install, using cold solvent welded joints which require no special tools.

## application guide

- Temperature range 0°C to 60°C
- Abrasion resistant
- Non-toxic and taint free
- Rigid pipes - no special support needed
- Ideal for above and below ground use
- Resistant to many inorganic chemicals
- Threading possible
- Resistant to most solutions of acids, alkalis and salts
- Sizes from 1/4" to 24" and 10mm to 630mm
- No special tools required for installation
- Jointing by cold solvent welding or rubber ring mechanical joints
  
- Not resistant to aromatic and chlorinated hydrocarbons

## standards and approvals

We offer a wide range of systems to leading international standards:

Pipe (inch sizes)	: EN 1452
	: ASTM D 1785
	: ASTM D 2241
Pipe (mm sizes)	: EN 1452
	: DIN 8061/2
Fittings (inch sizes)	: BSEN 1452-3
	: ASTM D2467
	: ASTM D 2466
Fittings (mm sizes)	: DIN 8063
Threaded Fittings	: BS21/DIN 2199/ISO 727
	: ASTM D 2464

Pipes, fittings and solvent cements are WRAS listed for use in contact with cold potable water.

## section guide

Pipe - Inch Size	26
Solvent Cement, Primer, Cleaner	29
Plain Fittings - Inch Size	30
Flanges - Inch Size	40
Adaptor Fittings - Inch Size	41
Threaded Fittings - Inch Size	50
Saddles - Inch Size	56
Netvite Clamp System - Inch Size	59
Clear Pipe & Fittings	60
FlexFit Flexible Pipe & Fittings	62
Hose Insert Fittings	64
Pipe - mm Size	66
Plain Fittings - mm Size	69
Flanges - mm Size	75
Adaptor Fittings - mm Size	77
Saddles - mm Size	82
Netvite Clamp System - mm Size	83
Ball Valve, Double Union	86
Ball Valve Brackets, Double Union	88
Ball Valve, True Union	89
Ball Valve Brackets, True Union	90
Ball Valve, Single Union	92
Ball Valve, Economy Utility	94
Dosing Valve	96
Ball Valve, Economy Compact	96
Ball Valve, Economy Double Union	97
Ball Valve, T-Port	98
Ball Valve, L-Port	99
Butterfly Valve	102
Diaphragm Valve	110
Gauge Guard	112
Needle Valve	114
Y-Pattern Valve	115
Slide Gate Valve	116
Gate Valve	117
Non-Return Valve, Check	118
Air Release Valve	122
Foot Valve	123
Non-Return Valve, Wafer Check	126
Swing Check Valve	128
Basket Strainer	130
Line Strainer	131
Y-Strainer	132
Ball Valve, Electrically Actuated	134
Ball Valve, T-Port, Electrically Actuated	137
Ball Valve, Pneumatically Actuated	138
Diaphragm Valve, Actuated	142
Butterfly Valve, Electrically Actuated	144
Butterfly Valve, Pneumatically Actuated	146
Pressure Reducing Valve	148
Pressure Relief Valve	152

### IPS Flow Systems

Seaham Grange Industrial Estate, Seaham, Co Durham, SR7 0PT, England

Tel: +44+ 191 521 3111 Fax: +44+ 191 521 3222

E-mail: sales@ipsflowsystems.com Website: www.ipsflowsystems.com